



An ISO 9001-2015 Certified Company

**Ultrasonic level Indicator & Transmitter**



Display : 4 Digit LCD  
Transmitter: 4-20mAmp+HART  
OutPut  
Relay : 1No+1NC  
Out put  
Supply : 230 VAC/24 VDC  
Enclosure : Flame Proof  
(IIA, IIB, IIC, T6)  
Range : 3 M, 8 M

Product Code : SD-ULITS

**Ultrasonic level Indicator & Transmitter**



Transmitter: 4-20mAmp+HART  
Out Put  
Relay : 1No+1NC  
Out put  
Supply : 230 VAC/24 VDC  
Enclosure : Flame Proof  
(IIA, IIB, IIC, T6)  
Range : 3 M, 8 M

Product Code : SD-ULITF

**Ultrasonic level Transmitter With Remote Indication**



Display : 4 Digit LCD  
Transmitter: 4-20 mAmp+HART  
Output  
Relay : 1No+1NC  
Out put  
Supply : 230 VAC/24 VDC  
Enclosure : Flame Proof  
(IIA, IIB, IIC, T6)  
Range : 3 M, 8 M

Product Code : SD-ULIT-2001


**Hydrostatic Level Indicator Transmitter**



Display : 4 Digit LCD  
Transmitter: 4-20 mAmp+HART  
Out Put  
Relay : 1 No + I NC  
Out Put  
Supply : 230 VAC/24 VDC  
Enclosure : Ex-Proof  
Range : Up to 100 M

Product Code : SD-SPLT

**Hydrostatic Level Indicator**



The Scientific Devices Hydrostatic Level Indicator is a robust diaphragm type Gauge with a dial read out. It is designed for easy on site adjustment to take account of varying liquid density. This Gauge requires no powers source and is suitable for fitting to tanks, which may be used for different liquids where the specific gravity may change. These externally mounted version is suitable for general application, though it is particularly suitable for

Product Code : HDLI

**Hydrostatic Level Transmitter With Remote Indication**



Display : 4 Digit LCD  
Transmitter: 4-20 mAmp+HART  
Out Put  
Supply : 230 VAC/24 VDC  
Enclosure : Ex-Proof  
Range : Up to 100 M

Product Code : SDPLT-PM-2001

**Capacitance level Indicator, Transmitter and High Low Switch**



Display : 4 Digit , LED/LCD  
Transmitter: 4-20 mAmp+HART  
Out Put  
Relay : 1 No + I NC  
Out Put  
Supply : 24 VDC  
Enclosure : Flame Proof  
(IIA, IIB, IIC, T6)  
Range : 3 M, 8 M

Product Code : CLT-I-HLS

**Capacitance level Indicator, Transmitter and High Low Switch**



Display : 4 Digit , LED/LCD  
Transmitter: 4-20 mAmp+HART  
Out Put  
Relay : 1 No + I NC  
Out Put  
Supply : 24 VDC  
Enclosure : Flame Proof  
(IIA, IIB, IIC, T6)

Product Code : CLT-I-HLS-R

**Side Mounted Hydrostatic Level Indicator Transmitter**



Display : 4 Digit , LED/LCD  
Transmitter: 4-20 mAmp+HART  
Out Put  
Relay : 1 No + I NC  
Out Put  
Supply : 24 VAC/24 VDC  
Enclosure : Ex-Proof  
Range : Up to 200 M

Product Code : SDSPLT-F-SM

**Side Mounted Hydrostatic Level Indicator Transmitter**



Display : 4 Digit , LED/LCD  
Transmitter: 4-20 mAmp+HART  
Out Put  
Relay : 1 No + I NC  
Out Put  
Supply : 24 VAC/24 VDC  
Enclosure : Ex-Proof  
Range : Up to 200 M

Product Code : SDSPLT-F-SM

**Radar level Indicator Transmitter**



Display : 4 Digit LCD  
Transmitter: 4-20 mAmp+HART  
Out Put  
Design : 250°C  
Temperature  
Supply : 24 VDC  
Enclosure : Ex-Proof  
Range : 35 M

Product Code : SD803

**Radar level Indicator Transmitter**



Display : 4 Digit LCD  
Transmitter: 4-20 mAmp+HART  
Out Put  
Design : 180°C  
Temperature  
Supply : 24 VDC  
Enclosure : Ex-Proof  
Range : 20 M

Product Code : SD802