



An ISO 9001-2015 Certified Company

**Differential Pressure Transmitter**



Pressure Range:0.10- 10 BAR  
Out-Put :4-20mA+HART  
Measuring Units:KPA, MPA, BAR,  
PSI, MMHG, MMH2O, MH2O,  
INH2O, FTH2O, INHG, MHG,  
TORR, MBAR, G/CM2, KG/CM2  
PA, ATM, MM, M  
Accuracy : +-0.075%  
Max Temperature:-40 to 120  
Deg C  
Power Supply: 24 VDC  
Diaphragm Material: SS316L,  
Hastalloy C

**Product Code : DPT-S**

**Pressure Indicator Transmitter**



Pressure range : -1 - 600 bar  
Out Put : 4-20 mA+HART  
Power Supply : 24 VDC  
Enclosure : IP 65  
Display : LCD  
Temperature : -20 - 120°C  
Burst Pressure : 300% FS  
Connection : Screwed  
Wetted part : SS304  
Diaphragm : SS316  
Accuracy : 0.25 % of FS

**Product Code : PIT-S**

**Pressure Indicator Transmitter**



Pressure range : -1 - 600 bar  
Out Put : 4-20 mA+HART  
Power Supply : 24 VDC  
Enclosure : IP 65  
Display : LCD  
Temperature : -20 - 120°C  
Burst Pressure : 300% FS  
Connection : Flanged  
Wetted part : SS304  
Diaphragm : SS316  
Accuracy : 0.25 % of FS

**Product Code : PIT-F**

**Pressure Transmitter**



Pressure range : -1 - 600 bar  
Out Put : 4-20 mA+HART  
Power Supply : 24 VDC  
Enclosure : IP 65  
Temperature : -20 - 120°C  
Burst Pressure : 300% FS  
Connection : screwed  
Wetted part : SS304  
Diaphragm : SS316  
Accuracy : 0.25 % of FS

**Product Code : PTX-S**

**Mini Pressure Indicator Transmitter**



Pressure range : -1 - 600 bar  
Out Put : 4-20 mA+HART  
Power Supply : 24 VDC  
Enclosure : IP 65  
Display : LCD  
Temperature : -20 - 85°C  
Burst Pressure : 300% FS  
Connection : ½" NPT (M)  
Wetted part : SS304  
Diaphragm : SS316  
Accuracy : 0.25 % of FS

**Product Code : PTXM-S-LCD**

**Mini Pressure Transmitter**



Pressure range : -1 - 600 bar  
Out Put : 4-20 mA+HART  
Power Supply : 24 VDC  
Enclosure : IP 65  
Temperature : -20 - 85°C  
Burst Pressure : 300% FS  
Connection : ½" NPT (M)  
Wetted part : SS304  
Diaphragm : SS316  
Accuracy : 0.25 % of FS

**Product Code : PTXM-S**

**Hydrostatic Level Indicator Transmitter**



Display : 4 Digit LCD  
Range : Up to 100 M  
Transmitter : 4-20  
mA+HART  
Out Put  
Relay : 1 No + I NC  
Out Put  
Supply : 230 VAC/24 VDC  
Enclosure : Ex-Proof

**Product Code : SD-SPLT**

**Hydrostatic Level Transmitter**



Transmitter : 4-20mA+HART  
Out Put  
Range : Up to 100 M  
Accuracy : 0.2%0.5%  
Supply : 230 VAC/24 VDC

**Product Code : SD-HLT**

**Pressure Switch**



Display : LCD  
Range : 0.01 - 400Bar(G)  
0.10 - 100 Bar (A)  
Transmitter : 4-20mA /  
PNP or NPN Out Put  
Measuring Units:KPA, MPA, BAR,  
PSI, MMHG, MMH2O, MH2O,  
INH2O, FTH2O, INHG, MHG,  
TORR, MBAR, G/CM2, KG/CM2 PA,  
ATM, MM, M  
Accuracy : 0.2%0.5%  
Supply : 230 VAC/24 VDC

**Product Code : SD-PRSW**

**Differential Pressure Transmitter**



Pressure Range:0.10 - 10 BAR  
Out-Put :4-20mA+HART  
Measuring Units:KPA, MPA,  
BAR, PSI, MMHG, MMH2O,  
MH2O,  
INH2O, FTH2O, INHG, MHG,  
TORR, MBAR, G/CM2, KG/CM2  
PA, ATM, MM, M  
Accuracy : +-0.075%  
Max Temperature:-40 to 120  
Deg C  
Power Supply: 24 VDC  
Diaphragm Material: SS316L,  
Hastalloy C

**Product Code : DPT-F**

**Sanitary Pressure Transmitter**



Pressure Range:0.10 - 30  
BAR(G) / 0.10 - 10 BAR (A)  
Out-Put :4-20mA+HART  
Measuring Units:KPA, MPA,  
BAR, PSI, MMHG, MMH2O,  
MH2O,  
INH2O, FTH2O, INHG, MHG,  
TORR, MBAR, G/CM2, KG/CM2  
PA, ATM, MM, M  
Accuracy : 0.2%0.5%  
Max Temperature:-40 to 120  
Deg C  
Power Supply: 24 VDC  
Diaphragm Material: SS316L,

**Product Code : PTXM-TC-LCD**

**Temperature Transmitter**



Power Supply: 24 VDC  
Out put :4-20mA+HART  
Connection : Screwed  
Probe length: Customized

**Product Code :  
TT-AS**



**Product Code :  
TIT-AS**